

## ***Decks – Single Family Homes***

Note: Section 26 & 30 – Attached Washington Homes in Overland Park are included in this section.

### ***General Considerations***

A deck shall be an appropriate size for the area in which it is to be located. It shall be harmonious in configuration, detail, material and color with the architecture of the house.

Modifications or additions to an existing deck must incorporate the same materials, colors and detailing as the approved existing deck.

### ***Specific Guidelines***

- Design and location should minimize any tree removal.
- Changes in grade or drainage pattern must not adversely affect adjoining properties.
- Decks are to be located at the rear of the house.
- Upper-level decks shall be attached directly to the house. Only ground level decks may be approved as freestanding decks.
- Decks should not project beyond the sidewalls of the house. The sidewalls of the house are defined as the major (structural) side walls and do not include bay windows, chimney enclosures, porches or other such projections. In certain situations, stairs and some portions of the deck may extend up to 4' beyond the sidewalls.
- Privacy screens, arbors, trellises, gazebos, screened porches or similar structures of significant mass shall not be located on any portion of a deck that projects beyond the side of the house.
- Plant hangers will be considered on a case-by-case basis.
- Diagonal or similar braces are not allowed for lateral support.
- Lighted and/or solar post caps will be considered on a case-by-case basis.
- A solid trim board shall be provided on any open side of the deck to conceal the joists and cut ends of the decking.
- Underdeck screening should be compatible with the architecture of the house and deck. Any underdeck screening must have finished edging. If lattice is used, it must be properly framed and recessed.
- Decks are to be constructed of wood or composite material such as “Trex®”. Only wood tone colors are allowed. Other materials will be considered on a case-by-case basis.
- Wood decks may be left to weather naturally however; if the resident desires to stain, paint or change the existing color of their deck an application is required for approval. If a clear preservative sealer is used an application is not required.
- The standard railing design is a simple 2” x 2” vertical picket railing at the minimum height required by County Code. Decorative railings and balusters will be considered on a case-by-case basis.
- Privacy screens should be constructed of lattice that is properly framed and installed directly on top of the railing. The total height of the railing and privacy screen must not exceed 7’-0” above the deck floor.

BROADLANDS  
*Modifications Subcommittee Design Guidelines*

**Decks – continued**

- For **detached homes**, privacy screens should be limited to small areas of the deck. As a guideline, the total amount (length) of privacy screening should be limited to no more than 30% of the length of the deck.
- For enclosed upper level decks such as screened porches, see also the design guidelines for porches/screened porches and additions/alterations (Major).

***Submission Requirements***

- A copy of the existing site plan/plat showing the house, property lines, easements, significant vegetation, existing patios and decks, fencing, accessory structures and illustrating the location of the proposed deck
- Photographs showing the house and site marked to show the location of the proposed deck
- Detailed drawings of the deck to scale and dimensions, showing the house and the proposed deck
- For upper level decks and decks of more than one level, provide elevation drawings to scale, showing the house and the proposed deck, including the height above grade, stairs and any other proposed elements
- Detailed drawings of railings and any benches, planters, privacy screens, etc. including dimensions
- Materials and samples of proposed colors if other than pressure treated wood
- If lighting is used on deck posts or stair risers, submit photos of lights and wattage
- A landscape plan, as applicable

**Decks – Townhomes**

***General Considerations***

A deck shall be an appropriate size for the area in which it is to be located. It shall be harmonious in configuration, detail, material and color with the architecture of the house.

Modifications or additions to an existing deck must incorporate the same materials, colors, and detailing as the approved existing deck.

***General Guidelines – Please see specific guidelines for your section***

- Changes in grade or drainage pattern must not adversely affect adjoining properties.
- Decks are to be located at the rear of the house.
- Upper-level decks shall be attached directly to the house. Only ground level decks may be approved as freestanding decks.
- Plant hangers will be considered on a case-by-case basis.
- Stairs should be parallel or perpendicular to the edge of the deck or be set immediately adjacent to the deck in an L-shaped configuration.
- Spiral stairs will be considered on a case-by-case basis.
- Diagonal or similar braces are not allowed for lateral support.

BROADLANDS  
*Modifications Subcommittee Design Guidelines*

**Decks – continued**

- A solid trim board shall be provided on any open side of the deck to conceal the joists and cut ends of the decking.
- Under deck screening is prohibited.
- Lighted and/or solar post caps will be considered on a case-by-case basis.
- Decks shall be constructed of either a wood tone composite material such as Trex®, or wood.
- Railings and other features such as privacy screens for attached housing must match the standard for the specific section.
- If a railing standard does not exist, a simple 2" x 2" vertical picket railing at the minimum height required by County Code is recommended.
- Privacy screens should be constructed of lattice, properly framed and installed directly on top of the railing. Any lattice privacy screens must be no taller than 4'-0" above the deck rail. The total height of the railing and privacy screen must not exceed 7'-0" above the deck floor.
- Privacy screens may be installed only on the side railings of the deck. They may be installed on either or both sides of the deck railing and may not exceed 8' in length on each side of the deck. No privacy screening is allowed on the rear of the deck.

**Deck Landing Standards - All Townhouse Sections**

Where there is no access from the basement of the house, a second-floor landing with stairs is approved as follows:

- In order to maintain a consistent visual harmony within the cluster, the design of any second-floor landing, including size, materials and details, must be in conformance with the design of the Modification Subcommittee's approved standard landings for the cluster.
- The landing shall not exceed 50 square feet in size. The maximum width of the landing is 8', and the depth of the landing shall not exceed the width.
- The landing must be set back at least 1' from any common property line so that adjacent landings and/or decks are at least 2' apart.
- Railing pickets must be 2" x 2" vertical members, without decorative elements such as sunbursts or other patterns.
- Although stairs are recommended to be parallel or perpendicular to the edge of the landing or to be set immediately adjacent to the deck in an L-shaped configuration, depending upon the height of the landing above the ground, other stair configurations may be considered.
- Stairs shall not project beyond the sidewalls of the house.
- Landings must match the deck in same color, style, design and appearance.

***Submission Requirements***

- A copy of the existing site/plat plan showing the house, property lines, easements, significant vegetation, existing patios and decks, fencing, accessory structures and illustrating the location of the proposed deck.
- Photographs showing the house and site marked to show the location of the proposed deck.

BROADLANDS  
*Modifications Subcommittee Design Guidelines*

**Decks – continued**

- Detailed drawings of the deck to scale, and dimensions showing the house and the proposed deck.
- For upper level decks and decks of more than one level, provide elevation drawings to scale, showing the house and the proposed deck including the height above grade, stairs and any other proposed elements.
- Detailed drawings of railings and any benches, planters, privacy screens, etc. including dimensions.
- Materials and samples of proposed colors if other than pressure treated wood.
- If lighting is used on deck posts or stair risers, submit photos of lights and wattage.
- A landscape plan, as applicable.

## ***Guidelines for Specific Sections***

### **Deck Design Standards - Section 3 – Van Metre Townhouses**

- In order to maintain a consistent visual harmony within the cluster, the design of any upper deck including size, materials and details, must be in conformance with the design of the Modifications Subcommittee’s approved standard deck for the cluster.
- The approved minimum deck size is 8’ deep x 12’ wide. The approved maximum deck size is 12’ deep x 18’ wide for 20’ wide units and 12’ deep x 20’ wide for 22’ wide units.
- Where a deck must be set back from the rear of the house due to the existing location of a utility and/or mechanical equipment, the depth of the deck may be extended by the required depth of the offset, up to a maximum of 4’.
- Decks must be set back at least 1’ from any common property line so that adjacent decks are at least 2’ apart.
- The outer corners can be cut off at a 45-degree angle approximately 2’ x 2’ in size.
- Railing pickets must be 2” x 2” vertical members, without decorative elements such as sunbursts or other patterns.
- Stairs are recommended to be located perpendicular to the rear wall of the house and parallel and along the side of the deck.
- Stairs may also be approved in an L-shaped configuration where they are parallel to both the side and rear of the deck.
- Stairs must be located within the maximum approved deck width.
- Wood decks may be left to weather naturally. If a clear preservative sealer is used an application is not required. If the deck is to be stained a color or there is a change to the existing color, an application is required. Semitransparent or opaque stains in a wood tone are allowed. White decks are only allowed when composite materials are used. White paint and white stain are prohibited. Two-toned railings are also not permitted.
- Rejuvenation products such as “Deck Over” are also allowed. Rough texture must be used only on horizontal surfaces. Smooth texture may be used on entire deck. Only wood tone colors are allowed.

### **Deck Design Standards - Section 7 – Ryland Townhouses**

- In order to maintain a consistent visual harmony within the cluster, the design of any upper deck including size, materials and details, must be in conformance with the design of the Modifications Subcommittee’s approved standard deck for the cluster.

BROADLANDS  
*Modifications Subcommittee Design Guidelines*

**Decks – continued**

- The approved deck sizes for units with sunrooms are 8’ wide x 10’ deep for 20’ wide units and 10’ wide x 10’ deep for 22’ wide units.
- The approved minimum deck size for units without sunrooms is 10’ deep x 12’ wide. The approved maximum deck size for units without sunrooms is 12’ deep x 18’ wide for 20’ wide units and 12’ deep x 20’ wide for 22’ wide units.
- Where a deck must be set back from the rear of the house due to the existing location of a utility and/or mechanical equipment, the depth of the deck may be extended by the required depth of the offset up to a maximum of 4’.
- Decks must be set back at least 1’ from any common property line so that adjacent decks are at least 2’ apart.
- For decks at units without sunrooms, the outer corners can be cut off at a 45 degree angle approximately 2’ x 2’ in size.
- Railing pickets must be 2” x 2” vertical members, without decorative elements such as sunbursts or other patterns.
- Stairs are recommended to be located perpendicular to the rear wall of the house and parallel and along the side of the deck.
- Stairs may also be approved in an L-shaped configuration where they are parallel to both the side and rear of the deck.
- Stairs must be located within the maximum approved deck width.
- Wood decks may be left to weather naturally. If a clear preservative sealer is used an application is not required. If the deck is to be stained a color or there is a change to the existing color, an application is required. Semitransparent or opaque stains in a wood tone are allowed. White decks are only allowed when composite materials are used. White paint and white stain are prohibited. Two-toned railings are also not permitted.
- Rejuvenation products such as “Deck Over” are also allowed. Rough texture must be used only on horizontal surfaces. Smooth texture may be used on entire deck. Only wood tone colors are allowed.

**Deck Design Standards - Section 8 & 10 – Miller and Smith Townhouses**

- In order to maintain a consistent visual harmony within the cluster, the design of any upper deck including size, materials and details, must be in conformance with the design of the Modifications Subcommittee’s approved standard deck for the cluster.
- The approved minimum deck size is 10’ deep x 12’ wide. The approved maximum deck size for interior units is 12’ deep x 16’ wide; the approved maximum deck size for exterior units is 12’ deep x 18’ wide.
- Where a deck must be set back from the rear of the house due to the existing location of a utility and/or mechanical equipment, the depth of the deck may be extended by the required depth of the offset up to a maximum of 4’.
- Decks must be set back at least 1’ from any common property line so that adjacent decks are at least 2’ apart.
- The outer corners of the deck are square or can be cut off at a 45 degree angle approximately 2’ x 2’ in size.
- Railing pickets must be 2” x 2” vertical members without decorative elements such as sunbursts or other patterns.
- Stairs are recommended to be located perpendicular to the rear wall of the house and parallel and along the side of the deck.

BROADLANDS  
*Modifications Subcommittee Design Guidelines*

**Decks – continued**

- Stairs may also be approved in an L-shaped configuration where they are parallel to both the side and rear of the deck.
- Stairs must be located within the maximum approved deck width.
- Wood decks may be left to weather naturally. If a clear preservative sealer is used an application is not required. If the deck is to be stained a color or there is a change to the existing color, an application is required. Semitransparent or opaque stains in a wood tone are allowed. White decks are only allowed when composite materials are used. White paint and white stain are prohibited. Two-toned railings are also not permitted.
- Rejuvenation products such as “Deck Over” are also allowed. Rough texture must be used only on horizontal surfaces. Smooth texture may be used on entire deck. Only wood tone colors are allowed.

**Deck Design Standards - Section 11 & 34 – Engle Homes Townhouses**

- In order to maintain a consistent visual harmony within the cluster, the design of any upper deck including size, materials and details, must be in conformance with the design of the Modifications Subcommittee’s approved standard deck for the cluster.
- The approved minimum deck size for the *Pinehurst* (exterior unit) is 10’ deep x 16’ wide. The approved maximum decks size for the *Pinehurst* (exterior unit) is 12’ deep x 20’ wide.
- The approved minimum deck size for the *Somerset* and *Devonshire* (interior units) is 10’ deep x 10’ wide. The approved maximum deck size for the *Somerset* and *Devonshire* (interior units) is 12’ deep x 18’ wide.
- Rejuvenation products such as “Deck Over” are also allowed. Rough texture must be used only on horizontal surfaces. Smooth texture may be used on entire deck. Only wood tone colors are allowed.
- The approved deck size for the *Somerset* and *Devonshire* (interior units) with sunrooms is 7’ wide x 10’ or 12’ deep. A deck extension is also approved for *Somerset* and *Devonshire* (interior units) with sunrooms that extends 10’ beyond the rear wall of the sunroom and is 18’ in width. The deck does not require a property line setback on the recessed side (where it is an extension of the sunroom deck); however, it must be set at least 2’ from the common property line on the sunroom side of the house.
- Where a deck must be set back from the rear of the house due to the existing location of utility and/or mechanical equipment, the depth of the deck may be extended by the required depth of the offset, up to a maximum of 4’.
- Decks must be set back at least 1’ from any common property line so that adjacent decks are at least 2’ apart.
- In all cases the outer corners of the deck are square or can be cut off at a 45 degree angle approximately 2’ x 2’ in size.
- Railing pickets must be 2” x 2” vertical members without decorative elements such as sunbursts or other patterns.
- Stairs are recommended to be located perpendicular to the rear wall of the house and parallel and along the side of the deck.
- Stairs may also be approved in an L-shaped configuration where they are parallel to both the side and rear of the deck.
- Stairs must be located within the maximum approved deck width.
-

BROADLANDS  
*Modifications Subcommittee Design Guidelines*

**Decks – continued**

- Wood decks may be left to weather naturally. If a clear preservative sealer is used an application is not required. If the deck is to be stained a color or there is a change to the existing color, an application is required. Semitransparent or opaque stains in a wood tone are allowed. White decks are only allowed when composite materials are used. White paint and white stain are prohibited. Two-toned railings are also not permitted.
- Rejuvenation products such as “Deck Over” are also allowed. Rough texture must be used only on horizontal surfaces. Smooth texture may be used on entire deck. Only wood tone colors are allowed.

**Deck Design Standards - Section 34 – Miller and Smith Townhouses**

- In order to maintain a consistent visual harmony within the cluster, the design of any upper deck including size, materials and details, must be in conformance with the design of the Modifications Subcommittee’s approved standard deck for the cluster.
- Due to the unique design of these units, deck size is restricted. The approved deck size for interior units is 11’ deep x 12’ wide; the approved deck size for exterior or end units is 10’ deep x 13’ wide.
- Exterior or end unit decks may not wrap around the rear corner of the unit (so as to avoid facing the rear of the adjacent interior unit).
- Interior unit decks must be set back 1’ from the common property line.
- In all cases, the outer corners of the deck are square or can be cut off at a 45 degree angle approximately 2’ x 2’ in size.
- Railing pickets must be 2” x 2” vertical members without decorative elements such as sunbursts or other patterns.
- On interior units, stairs are to be located parallel to the rear of the deck; on exterior or end units, stairs may be located parallel to the rear or side of the deck on the side away from the adjacent interior unit.
- On exterior or end units, stairs may also be approved in an L-shaped configuration where they are parallel to both the side and rear of the deck.
- Wood decks may be left to weather naturally. If a clear preservative sealer is used an application is not required. If the deck is to be stained or there is a change to the existing color, an application is required. Semitransparent or opaque stains in a wood tone are allowed. White decks are only allowed when composite materials are used. White paint and white stain are prohibited. Two-toned railings are also not permitted.
- Rejuvenation products such as “Deck Over” are also allowed. Rough texture must be used only on horizontal surfaces. Smooth texture may be used on entire deck. Only wood tone colors are allowed.

**Deck Design Standards - Sections 54, 56, 58, 60 – Van Metre Townhouses**

- In order to maintain a consistent visual harmony within the cluster, the design of any upper deck including size, materials and details, must be in conformance with the design of the Modifications Subcommittee’s approved standard deck for the cluster.
- The approved minimum deck size is 10’ deep x 12’ wide.
- For units without sunrooms, the approved maximum deck size is:
  - 20’ wide units: 12’ deep x 18’ wide
  - 22’ wide units: 12’ deep x 20’ wide
  - 24’ wide units: 12’ deep x 22’ wide

BROADLANDS  
*Modifications Subcommittee Design Guidelines*

**Decks – continued**

- 28' wide units: 12' deep x 26' wide
- For units with sunrooms, the approved maximum deck size is the same as units without sunrooms, however, an *optional extension* is allowed as follows:
  - 20' wide units: 8' beyond the rear wall of the sunroom, 18' in width
  - 22' wide units: 8' beyond the rear wall of the sunroom, 20' in width
  - 24' wide units: 8' beyond the rear wall of the sunroom, 22' in width
  - 28' wide units: 8' beyond the rear wall of the sunroom, 26' in width
- Decks must be set back at least 1' from any property line so that adjacent decks are at least 2' apart.
- The outer corners of the deck are square or can be cut off at a 45 degree angle approximately 2' x 2' in size.
- Railing pickets must be 2" x 2" vertical members without decorative elements such as sunbursts or other patterns.
- Stairs are recommended to be located perpendicular to the rear wall of the house and parallel and along the side of the deck.
- Stairs may also be approved in an L-shaped configuration where they are parallel to both the side and rear of the deck.
- Stairs must be located within the maximum approved deck width.
- Wood decks may be left to weather naturally. If a clear preservative sealer is used an application is not required. If the deck is to be stained a color or there is a change to the existing color, an application is required. Semitransparent or opaque stains in a wood tone are allowed. White decks are only allowed when composite materials are used. White paint and white stain are prohibited. Two-toned railings are also not permitted.
- Rejuvenation products such as "Deck Over" are also allowed. Rough texture must be used only on horizontal surfaces. Smooth texture may be used on entire deck. Only wood tone colors are allowed.

**Deck Design Standards - Section 56 – Miller and Smith Townhouses  
(Newberry Street 20' wide and Beacon Hill 22' wide Models)**

- In order to maintain a consistent visual harmony within the cluster, the design of any upper deck including size, materials and details, must be in conformance with the design of the Modifications Subcommittee's approved standard deck for the cluster.
- For 20' wide units, the approved minimum deck size is 10' deep x 12' wide. The approved maximum deck size is 12' deep x 18' wide.
- For 22' wide units, the approved minimum deck size is 10' deep x 12' wide. The approved maximum deck size is 12' deep (measured from the back wall of the breakfast area bump out) x 20' wide.
- Decks must be set back at least 1' from any common property line so that adjacent decks are at least 2' apart.
- The outer corners of the deck are square or can be cut off at a 45 degree angle approximately 2' x 2' in size.
- Railing pickets must be 2" x 2" vertical members without decorative elements such as sunbursts or other patterns.
- Stairs are recommended to be located perpendicular to the rear wall of the house and parallel and along the side of the deck.

BROADLANDS  
*Modifications Subcommittee Design Guidelines*

- **Decks** – *continued*
- Stairs may also be approved in an L-shaped configuration where they are parallel to both the side and rear of the deck.
- Stairs must be located within the maximum approved deck width.
- Wood decks may be left to weather naturally. If a clear preservative sealer is used an application is not required. If the deck is to be stained a color or there is a change to the existing color, an application is required. Semitransparent or opaque stains in a wood tone are allowed. White decks are only allowed when composite materials are used. White paint and white stain are prohibited. Two-toned railings are also not permitted.
- Rejuvenation products such as “Deck Over” are also allowed. Rough texture must be used only on horizontal surfaces. Smooth texture may be used on entire deck. Only wood tone colors are allowed.

**Deck Extension Design Standards - Section 56 – Miller and Smith Townhouses (Wyndermere 28’ wide Model)**

- In order to maintain a consistent visual harmony within the cluster, the design of any upper deck including size, materials and details, must be in conformance with the design of the Modifications Subcommittee’s approved standard deck for the cluster.
- An extension of the main level deck may be constructed. The extension may project up to 8’ from the family room rear wall and be a maximum of 26’ wide.
- No extension of the bedroom level deck is permitted.
- Deck extensions must be set back at least 1’ from any common property line so that adjacent decks are at least 2’ apart.
- The outer corners of the deck are square or can be cut off at a 45 degree angle approximately 2’ x 2’ in size.
- Railing pickets must be 2” x 2” vertical members without decorative elements such as sunbursts or other patterns.
- Stairs are recommended to be located perpendicular to the rear wall of the house and parallel and along the side of the deck.
- Stairs may also be approved in an L-shaped configuration where they are parallel to both the side and rear of the deck.
- Stairs must be located within the maximum approved deck width.
- Deck railings must be painted or wrapped in vinyl to match the existing color. Flooring and trim board must remain unfinished to weather naturally or may be treated with a clear preservative. Post must be topped with a matching post cap.

**Deck Design Standards - Section 200 – Broadlands Station Van Metre Townhouses**

- In order to maintain a consistent visual harmony within the cluster, the design of any upper deck, including size, materials and details, must be in conformance with the design of the Modifications Subcommittee’s approved standard deck for the cluster.
- The approved maximum deck width for a:  
20’ wide lot is 18’ wide  
18’ wide lot is 16’ wide
- Maximum allowed depth varies by lot. Please refer to **Broadlands Station Phase 1 & Phase 2** deck exhibits for maximum depth allowed on your lot or call the Broadlands Homeowners Association for assistance.
- For lots located on Pagoda Terrace the approved maximum deck depth is 12’.

BROADLANDS  
*Modifications Subcommittee Design Guidelines*

- **Decks** – *continued*
- Decks may not be built within 5’ of the rear property line.
- Decks must be set back at least 1’ from any common property line so that adjacent decks are at least 2’ apart.
- The outer corners of the deck are square or can be cut off at a 45 degree angle approximately 2’ x 2’ in size.
- Railing pickets must be 2” x 2” vertical members, without decorative elements such as sunbursts or other patterns.
- Stairs are recommended to be located perpendicular to the rear wall of the house and parallel and along the side of the deck.
- Stairs may also be approved in an L-shaped configuration where they are parallel to both the side and rear of the deck.
- Stairs must be located within the maximum approved deck width.
- Wood decks may be left to weather naturally. If a clear preservative sealer is used an application is not required. If the deck is to be stained a color or there is a change to the existing color, an application is required. Semitransparent or opaque stains in a wood tone are allowed. White decks are only allowed when composite materials are used. White paint and white stain are prohibited. Two-toned railings are also not permitted.
- Rejuvenation products such as “Deck Over” are also allowed. Rough texture must be used only on horizontal surfaces. Smooth texture may be used on entire deck. Only wood tone colors are allowed.